

# CRANE 3S Camera Compatibility List

Updated on March 19th, 2020

| Camera Model   | Photo |          | Video |          | Live Preview | Shutter Speed Adjustment |            | Aperture Adjustment |            | ISO Adjustment |            | EV Adjustment |            | Electronic Zoom | Halfway Press Shutter Button to Autofocus | Electronic Follow Focus(Focus Wheel) | Camera Control Cable Type   | Camera Firmware Version | Note   |
|----------------|-------|----------|-------|----------|--------------|--------------------------|------------|---------------------|------------|----------------|------------|---------------|------------|-----------------|---|--------------------------------------|-----------------------------|-------------------------|--|
|                | Save  | Playback | Save  | Playback |              | Photo Mode               | Video Mode | Photo Mode          | Video Mode | Photo Mode     | Video Mode | Photo Mode    | Video Mode |                 |   |                                      |                             |                         |  |
| Sony a9        | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V5.00                   | 1. Please select "PC Remote" for your camera's "USB Connection".   |
| Sony a7R4      | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V1.00                   |  |
| Sony a7R3      | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V3.01                   |  |
| Sony a7M3      | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V3.01                   |  |
| Sony a7R2      | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V4.00                   |  |
| Sony a7M2      | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V3.00                   |  |
| Sony a7S2      | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V3.00                   |  |
| Sony a6600     | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V1.00                   |  |
| Sony a6500     | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V1.06                   |  |
| Sony a6400     | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V2.00                   |  |
| Sony a6300     | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V2.01                   |  |
| Sony a6100     | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V1.00                   |  |
| Sony a6000     | √     | √        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | √               | -   | -                                    | Type-C to Multi USB         | V3.21                   |  |
| Panasonic G9   | √     | √        | √     | √        | -            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | √   | ×                                    | Type-C to Micro USB         | V2.1                    | 1. Please select PC(Tether) for your camera's "USB mode".<br>2. When using electronic focusing, the camera lens should be in "MF" mode.  |
| Panasonic GH5  | √     | √        | √     | √        | -            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | √   | ×                                    | Type-C to Type-C USB        | V2.5                    |  |
| Panasonic GH5S | √     | √        | √     | √        | -            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | √   | ×                                    | Type-C to Type-C USB        | V1.5                    |  |
| Panasonic S1   | √     | √        | √     | √        | -            | ×                        | ×          | ×                   | ×          | ×              | ×          | ×             | ×          | -               | -   | ×                                    | Type-C to Type-C USB        | V1.3                    |  |
| Panasonic S1H  | √     | √        | √     | √        | -            | ×                        | ×          | ×                   | ×          | ×              | ×          | ×             | ×          | -               | -   | ×                                    | Type-C to Type-C USB        | V1.0                    |  |
| Canon 1DX2     | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | (Unavailable in Live View mode)           | ×                                    | Type-C to Micro USB         | V1.0.2                  | 1. Please apply electronic follow focus function in AF mode of the lens and live view mode of the camera<br>2. If using electronic focusing when recording a video, please "Disable" the " Movie Servo AF ". |
| Canon 5D3      | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | (Unavailable in Live View mode)           | ×                                    | Type-C to Mini USB          | V1.3.5                  |  |
| Canon 5D4      | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | (Unavailable in Live View mode)           | ×                                    | Type-C to Micro USB         | V1.0.4                  |  |
| Canon 5DS      | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | (Unavailable in Live View mode)           | ×                                    | Type-C to Micro USB         | V1.1.1                  |  |
| Canon 5DS R    | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | (Unavailable in Live View mode)           | ×                                    | Type-C to Micro USB         | V1.1.2R                 |  |
| Canon 6D       | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | (Unavailable in Live View mode)           | ×                                    | Type-C to Mini USB          | V1.1.8                  |  |
| Canon 6D2      | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | (Unavailable in Live View mode)           | ×                                    | Type-C to Mini USB          | V1.0.4                  |  |
| Canon 80D      | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | (Unavailable in Live View mode)           | ×                                    | Type-C to Mini USB          | V1.0.2                  |  |
| Canon 90D      | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | (Unavailable in Live View mode)           | ×                                    | Type-C to Micro USB         | V1.0.0                  |  |
| Canon EOS R    | √     | √        | √     | √        | -            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | -   | ×                                    | Type-C to Type-C USB        | V1.6.0                  |  |
| Canon EOS RP   | √     | √        | √     | √        | -            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | -   | ×                                    | Type-C to Type-C USB        | V1.4.0                  |  |
| Nikon D850     | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | √   | ×                                    | Type-C to Micro USB         | V1.10                   | 1. When using electronic focusing, the camera lens should be in A(AF) mode and select AF-S or AF-C in focusing mode.   |
| Nikon Z6       | √     | √        | √     | √        | -            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | √   | ×                                    | Type-C to Type-C USB        | V2.01                   |  |
| Nikon Z7       | √     | √        | √     | √        | -            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | √   | ×                                    | Type-C to Type-C USB        | V2.00                   |  |
| Nikon Z50      | √     | √        | √     | √        | √            | √                        | √          | √                   | √          | √              | √          | √             | √          | -               | √   | ×                                    | Type-C to Micro USB         | V1.00                   |  |
| Canon C200     | -     | -        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | -               | -   | -                                    | Type-C to φ2.5mm Plug       | V1.0.2.1.00             |  |
| Canon C300     | -     | -        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | -               | -   | -                                    | Type-C to φ2.6mm Male Jack  | V1.1.0.1.00             |  |
| Sony FS5       | -     | -        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | -               | -   | -                                    | Type-C to φ2.7mm Male Jack  | V1.01                   |  |
| Sony FS7M2     | -     | -        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | -               | -   | -                                    | Type-C to φ2.8mm Male Jack  | V1.22                   |  |
| Sony FX9       | -     | -        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | -               | -   | -                                    | Type-C to φ2.9mm Male Jack  |                         |  |
| Sony Z280      | -     | -        | √     | √        | -            | -                        | -          | -                   | -          | -              | -          | -             | -          | -               | -   | -                                    | Type-C to φ2.10mm Male Jack | V1.10                   |  |

| Camera Brand | Model   | Lens Model                 | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|---|----------------------------|--|--------------------|---------------------|---|---|
| Canon        | 1D X Mark II<br>(Without Backing Base)<br>5DS, 5DS R,<br>5D Mark IV,<br>5D Mark III, 6D Mark II,<br>6D, 90D, 80D; | EF 8-15mm f/4L USM         | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | EF 11-24mm f/4L USM        | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | EF 16-35mm f/4L IS USM     | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | EF 16-35mm f/2.8L III USM  | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | EF 17-40mm f/4L USM        | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | EF 24-70mm f/2.8L II USM   | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | EF 24-70mm f/4L IS USM     | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | EF 24-105mm f/4L IS II USM | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |

| Camera Brand                                     | Model   | Lens Model                     | Mounting Status                                  | Balance Adjustment                                | Camera Backing Base            | Servo Zoom/Focus Motor                            | Installation Remark   |
|--|---|--------------------------------|--|---|--------------------------------|---|---|
| Canon  | 1D X Mark II<br>(Without Backing Base)<br>5DS,<br>5DS R, 5D Mark IV,<br>5D Mark III, 6D Mark II,<br>6D, 90D, 80D; | EF 24-105mm f/3.5-5.6 IS STM   | Camera and Lens                                  | √   | -                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |   | EF 24mm f/1.4L II USM          | Camera and Lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |   | EF 35mm f/1.4L II USM          | Camera and Lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |   | EF 50mm f/1.2L USM             | Camera and Lens                                  | √   | √                              |   | No need to remove eyepiece cap                                      |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |   | EF 50mm f/1.4 USM              | Camera and Lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |   | EF 50mm f/1.8 STM              | Camera and Lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |   | EF 85mm f/1.2L II USM          | Camera and Lens                                  | √   | √                              |   | No need to remove eyepiece cap                                      |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |   | EF 85mm f/1.4L IS USM          | Camera and Lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |   | EF 85mm f/1.8 USM              | Camera and Lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |   | Sigma 24-70mm f/2.8 DG HSM Art | Camera and Lens                                  | √   | -                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |   |                                | Camera, Lens and Servo Motor (For Zoom Control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |   | Sigma 35mm f/1.4 DG HSM Art    | Camera and Lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
|  |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |   | Sigma 50mm f/1.4 DG HSM Art    | Camera and Lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
| Camera, Lens and Servo Motor (For Focus Control) | √   |                                | √  | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap |   |   |

| Camera Brand | Model   | Lens Model                 | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|---|----------------------------|--|--------------------|---------------------|---|---|
| Canon        | EOS R , EOSRP<br>(Non-RF lens should use EF-EOS R lens adapter) | EF 8-15mm f/4L USM         | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   | EF 11-24mm f/4L USM        | Camera and Lens                                  | √                  | √                   |   | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   | EF 16-35mm f/4L IS USM     | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   | EF 16-35mm f/2.8L III USM  | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   | EF 17-40mm f/4L USM        | Camera and Lens                                  | √                  | -                   |   | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   | EF 24-70mm f/2.8L II USM   | Camera and Lens                                  | √                  | √                   |   | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   | EF 24-70mm f/4L IS USM     | Camera and Lens                                  | √                  | √                   |   | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   | EF 24-105mm f/4L IS II USM | Camera and Lens                                  | √                  | √                   |   | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |

| Camera Brand | Model   | Lens Model                     | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|---|--------------------------------|--|--------------------|---------------------|---|---|
| Canon        | EOS R , EOSRP<br>(Non-RF lens should use EF-EOS R lens adapter) | EF 24-105mm f/3.5-5.6 IS STM   | Camera and Lens                                  | √                  | √                   |   | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   |                                | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length, Do not remove eyepiece cap |
|              |   | EF 24mm f/1.4L II USM          | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap                                      |
|              |   | EF 35mm f/1.4L II USM          | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap                                      |
|              |   | EF 50mm f/1.2L USM             | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap                                      |
|              |   | EF 50mm f/1.4 USM              | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap                                      |
|              |   | EF 50mm f/1.8 STM              | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   | EF 85mm f/1.2L II USM          | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   | EF 85mm f/1.4L IS USM          | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   | EF 85mm f/1.8 USM              | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap                                      |
|              |   | Sigma 24-70mm f/2.8 DG HSM Art | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   | Sigma 35mm f/1.4 DG HSM Art    | Camera and Lens                                  | √                  | -                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap                                      |
|              |   | Sigma 50mm f/1.4 DG HSM Art    | Camera and Lens                                  | √                  | -                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap                                      |
|              |   | RF15-35mm f/2.8 L IS USM       | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap                                      |
|              |   |                                | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap                                      |

| Camera Brand | Model   | Lens Model               | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark        |
|--------------|---|--------------------------|--|--------------------|---------------------|---|----------------------------|
| Canon        | EOS R , EOSRP<br>(Non-RF lens should use EF-<br>EOS R lens adapter) | RF24-70mm f/2.8 L IS USM | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap |
|              |   |                          | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap |
|              |   |                          | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap |
|              |   | RF24-105mm F4 L IS USM   | Camera and Lens                                  | √                  | -                   |   | Do not remove eyepiece cap |
|              |   |                          | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap |
|              |   |                          | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap |
|              |   | RF28-70mm F2 L           | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap |
|              |   |                          | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap |
|              |   |                          | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap |
|              |   | RF35mm F1.8              | Camera and Lens                                  | √                  | -                   |   | Do not remove eyepiece cap |
|              |   |                          | Camera, Lens and Servo Motor (For Focus Control) | √                  | -                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap |
|              |   | RF50mm F1.2 L USM        | Camera and Lens                                  | √                  | -                   |   | Do not remove eyepiece cap |
|              |   |                          | Camera, Lens and Servo Motor (For Focus Control) | √                  | -                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap |
|              |   | RF85mm F1.2 L USM        | Camera and Lens                                  | √                  | √                   |   | Do not remove eyepiece cap |
|              |   |                          | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Do not remove eyepiece cap |

| Camera Brand | Model                                | Lens Model                            | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|--------------------------------------|---------------------------------------|--|--------------------|---------------------|---|---|
| Nikon        | D850, D810,<br>D750, D610,<br>D7500; | AF-S NIKKOR 14-24mm f/2.8G ED         | Camera and lens                                  | √                  | √                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |                                      |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |                                      |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |                                      | AF-S NIKKOR 16-35mm f/4G ED VR        | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |                                      |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |                                      |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |                                      | AF-S Zoom-NIKKOR 17-35mm f/2.8D IF-ED | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |                                      |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |                                      |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |

| Camera Brand                                     | Model                          | Lens Model                            | Mounting Status                                  | Balance Adjustment                                | Camera Backing Base            | Servo Zoom/Focus Motor                            | Installation Remark   |
|--|--------------------------------|---------------------------------------|--|---|--------------------------------|---|---|
| Nikon  | D850, D810, D750, D610, D7500; | AF-S NIKKOR 18-35mm f/3.5-4.5G ED     | Camera and lens                                  | √   | -                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                | AF-S NIKKOR 24-70mm f/2.8E ED VR      | Camera and lens                                  | √   | -                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                | AF-S NIKKOR 24-70mm f/2.8G ED         | Camera and lens                                  | √   | -                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                | AF Zoom-NIKKOR 24-85mm f/2.8-4D IF    | Camera and lens                                  | √   | -                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                | AF-S NIKKOR 24-85mm f/3.5-4.5G ED VR  | Camera and lens                                  | √   | -                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                | AF-S NIKKOR 24-120mm f/4G ED VR       | Camera and lens                                  | √   | -                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                | AF-S NIKKOR 28-300mm f/3.5-5.6G ED VR | Camera and lens                                  | √   | -                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|  |                                | AF NIKKOR 14mm f/2.8D ED              | Camera and lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
|  |                                |                                       | Camera, Lens and Servo Motor (For Focus Control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|  |                                | AF-S NIKKOR 20mm f/1.8G ED            | Camera and lens                                  | √   | -                              |   | No need to remove eyepiece cap                                      |
| Camera, Lens and Servo Motor (For Focus Control) | √                              |                                       | √  | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap |   |   |

| Camera Brand | Model  | Lens Model                 | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|--|----------------------------|--|--------------------|---------------------|---|---|
| Nikon        | D850, D810, D750, D610, D7500;                   | AF-S NIKKOR 24mm f/1.4G ED | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |  | AF-S NIKKOR 24mm f/1.8G ED | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |  | AF-S NIKKOR 35mm f/1.4G    | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |  | AF-S NIKKOR 50mm f/1.4G    | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |  | AF-S NIKKOR 85mm f/1.4G    | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |  | AF-S NIKKOR 85mm f/1.8G    | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |  | Sigma 24 70mm f/2.8L DG    | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  | Sigma 35mm F1.4 DG         | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  | Sigma 50mm F1.4 DG         | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  | Z6, Z7;                    | NIKKOR Z 24-70mm f/2.8S                          | Camera and lens    | √                   | -   |   |
|              | Camera, Lens and Servo Motor (For Focus Control) |                            |  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              | Camera, Lens and Servo Motor (For Zoom Control)  |                            |  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              | NIKKOR Z 24-70mm f/4S                            |                            | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |                            | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              | NIKKOR Z 35mm f/1.8S                             |                            | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |  |                            | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |



| Camera Brand | Model   | Lens Model                            | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|---------|---------------------------------------|--|--------------------|---------------------|---|---|
| Nikon        | Z6, Z7; | NIKKOR Z 50mm f/1.8S                  | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | AF-S NIKKOR 14-24mm f/2.8G ED         | Camera and lens                                  | √                  | √                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | AF-S NIKKOR 16-35mm f/4G ED VR        | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | AF-S Zoom-NIKKOR 17-35mm f/2.8D IF-ED | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | AF-S NIKKOR 18-35mm f/3.5-4.5G ED     | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | AF-S NIKKOR 24-70mm f/2.8E ED VR      | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | AF-S NIKKOR 24-70mm f/2.8G ED         | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | AF Zoom-NIKKOR 24-85mm f/2.8-4D IF    | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | AF-S NIKKOR 24-85mm f/3.5-4.5G ED VR  | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |

| Camera Brand | Model   | Lens Model                            | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|---------|---------------------------------------|--|--------------------|---------------------|---|---|
| Nikon        | Z6, Z7; | AF-S NIKKOR 24-120mm f/4G ED VR       | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | AF-S NIKKOR 28-300mm f/3.5-5.6G ED VR | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | AF NIKKOR 14mm f/2.8D ED              | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | AF-S NIKKOR 20mm f/1.8G ED            | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | AF-S NIKKOR 24mm f/1.4G ED            | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | AF-S NIKKOR 24mm f/1.8G ED            | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | AF-S NIKKOR 35mm f/1.4G               | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | AF-S NIKKOR 50mm f/1.4G               | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | AF-S NIKKOR 85mm f/1.4G               | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | AF-S NIKKOR 85mm f/1.8G               | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | Sigma 24-70mm f/2.8L DG               | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         |                                       | Camera, Lens and Servo Motor (For Zoom Control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |         | Sigma 35mm F1.4 DG                    | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |         | Sigma 50mm F1.4 DG                    | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |         |                                       | Camera, Lens and Servo Motor (For Focus Control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |

| Camera Brand | Model   | Lens Model                  | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|---|-----------------------------|--|--------------------|---------------------|---|---|
| Sony         | A9,<br>A7R4, A7R3,<br>A7M3, A7R2,<br>A7M2, A7S2,<br>A6600, A6500,<br>A6400, A6300,<br>A6100, A6000; | FE 16-35mm F2.8 GM          | Camera and lens                                  | √                  | √                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | FE 16-35mm F4 ZAISS         | Camera and lens                                  | √                  | √                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | FE 12-24mm F4 G             | Camera and lens                                  | √                  | √                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | FE 24mm f1.4GM              | Camera and lens                                  | √                  | √                   |   | No need to remove eyepiece cap                                      |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |   | FE 24-70mm F2.8 GM          | Camera and lens                                  | √                  | √                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | FE 24-70mm F4 ZA OSS        | Camera and lens                                  | √                  | √                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                             | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | FE 28mm F2                  | Camera and lens                                  | √                  | √                   |   | No need to remove eyepiece cap                                      |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |   | FE 50mm F1.8                | Camera and lens                                  | √                  | √                   |   | No need to remove eyepiece cap                                      |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |   | FE 85mm F1.4 GM             | Camera and lens                                  | √                  | √                   |   | No need to remove eyepiece cap                                      |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |   | FE 85mm F1.8                | Camera and lens                                  | √                  | √                   |   | No need to remove eyepiece cap                                      |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |   | Distagon T* FE 35mm F1.4 ZA | Camera and lens                                  | √                  | √                   |   | No need to remove eyepiece cap                                      |
|              |   |                             | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |

| Camera Brand           | Model   | Lens Model                  | Mounting Status                                  | Balance Adjustment                                | Camera Backing Base            | Servo Zoom/Focus Motor                            | Installation Remark   |
|------------------------|---|-----------------------------|--|---|--------------------------------|---|---|
| Sony                   | A9,<br>A7R4, A7R3,<br>A7M3, A7R2,<br>A7M2, A7S2,<br>A6600, A6500,<br>A6400, A6300,<br>A6100, A6000; | Sonnar T* FE 35mm F2.8 ZA   | Camera and lens                                  | √   | √                              |   | No need to remove eyepiece cap                                      |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|                        |   | Planar T* FE 50mm F1.4 ZA   | Camera and lens                                  | √   | √                              |   | No need to remove eyepiece cap                                      |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|                        |   | Sonnar® T* FE 55mm F1.8 ZA  | Camera and lens                                  | √   | √                              |   | No need to remove eyepiece cap                                      |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|                        |   | E 10–18mm F4 OSS            | Camera and lens                                  | √   | √                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   |                             | Camera, lens and servo motor (for zoom control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   | E 16-70mm F4 ZA OSS         | Camera and lens                                  | √   | √                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   |                             | Camera, lens and servo motor (for zoom control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   | E PZ 18–105mm F4 G OSS      | Camera and lens                                  | √   | √                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   |                             | Camera, lens and servo motor (for zoom control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   | E 18–200mm F3.5–6.3 OSS LE  | Camera and lens                                  | √   | √                              |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   |                             | Camera, lens and servo motor (for zoom control)  | √   | √                              | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|                        |   | Sigma 16mm f/1.4 DC DN      | Camera and lens                                  | √   | √                              |   | No need to remove eyepiece cap                                      |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|                        |   | Sigma 24mm f1.4 DG          | Camera and lens                                  | √   | √                              |   | No need to remove eyepiece cap                                      |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|                        |   | Sigma 30mm f/1.4 DC HSM Art | Camera and lens                                  | √   | √                              |   | No need to remove eyepiece cap                                      |
|                        |   |                             | Camera, lens and servo motor (for focus control) | √   | √                              | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
| Sigma 30mm f/1.4 DC DN | Camera and lens   | √                           | √  |   | No need to remove eyepiece cap |   |   |
|                        | Camera, lens and servo motor (for focus control)  | √                           | √  | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap |   |   |

| Camera Brand | Model   | Lens Model   | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|---|--|--|--------------------|---------------------|---|---|
| Sony         | A9,<br>A7R4, A7R3,<br>A7M3, A7R2,<br>A7M2, A7S2,<br>A6600, A6500,<br>A6400, A6300,<br>A6100, A6000; | sigma 50mm f/1.4 DG                                | Camera and lens                                  | √                  | √                   |   | No need to remove eyepiece cap                                      |
|              |   |  | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |   | Sigma 56mm F1.4 DC DN                              | Camera and lens                                  | √                  | √                   |   | No need to remove eyepiece cap                                      |
|              |   |  | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |   | Tamron 28-75mm f/2.8                               | Camera and lens                                  | √                  | √                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |  | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |  | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter) | Camera and lens                                  | √                  | √                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |  | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; Need to remove eyepiece cap    |
|              |   |  | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; Need to remove eyepiece cap    |

| Camera Brand | Model   | Lens Model                        | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|---|-----------------------------------|--|--------------------|---------------------|---|---|
| FUJIFILM     | X-H1, X-T3,<br>X-T2, X-T30,<br>X-T20, X-T100; | XF 10-24mm f/4.0 R OIS            | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                                   | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                                   | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | XF 16-55mm f/2.8 R LM WR          | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                                   | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                                   | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | XF 18-55mm f/2.8-4 R OIS          | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                                   | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                                   | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | XF 18-135mm f/3.5-5.6 R LM OIS WR | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                                   | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                                   | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | XF 35mm f/2 R WR                  | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |   |                                   | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |

| Camera Brand | Model   | Lens Model                | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|---|---------------------------|--|--------------------|---------------------|---|---|
| FUJIFILM     | X-H1, X-T3,<br>X-T2, X-T30,<br>X-T20, X-T100; | XF 56mm f/1.2 R           | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |   |                           | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |   | XC 15-45mm f/3.5-5.6 OIS  | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                           | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                           | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | XC 16-50mm f/3.5-5.6 OIS  | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                           | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   |                           | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |   | Super EBC XF 23mm f/1.4 R | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |   |                           | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |

| Camera Brand | Model      | Lens Model                     | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|------------|--------------------------------|--|--------------------|---------------------|---|---|
| Panasonic    | GH5s, GH5; | Vario-Elmarit 8-18mm f/2.8-4.0 | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |            |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |            |                                | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |            | Vario 12-35mm f/2.8 II         | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |            |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |            |                                | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |            | Vario-Elmarit 12-60mm f/2.8-4  | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |            |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |            |                                | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |            | SUMMILUX 12mm f/1.4            | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |            |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |            | Lumix G 25mm f/1.7             | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |            |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |            | SUMMILUX 15mm f/1.7            | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |            |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |

| Camera Brand | Model  | Lens Model                               | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark   |
|--------------|--|--|--|--------------------|---------------------|---|---|
| Panasonic    | GH5s, GH5;                                       | MACRO 30mm f/2.8                         | Camera and lens                                  | √                  | -                   |   | No need to remove eyepiece cap                                      |
|              |  |  | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | No need to remove eyepiece cap                                      |
|              |  | M.ZUIKO DIGITAL ED 12-40mm f/2.8 PRO     | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |  | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |  | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  | M.ZUIKO DIGITAL ED 7-14mm f/2.8 PRO      | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |  | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |  | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  | M.Zuiko Digital ED 12-100mm f/4.0 IS PRO | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |  | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  |  | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              |  | S1H, S1;                                 | LUMIX S 24-105mm F/4 Macro OIS                   | Camera and lens    | √                   | √   |   |
|              | Camera, lens and servo motor (for focus control) |  |  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |
|              | Camera, lens and servo motor (for zoom control)  |  |  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length; No need to remove eyepiece cap |

| Camera Brand | Model  | Lens Model                     | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark                 |
|--------------|--------|--------------------------------|--|--------------------|---------------------|---|-------------------------------------|
| BMD          | BMPC4K | Vario-Elmarit 8-18mm f/2.8-4.0 | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length |
|              |        |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|              |        |                                | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|              |        | Vario 12-35mm f/2.8 II         | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length |
|              |        |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|              |        |                                | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|              |        | Vario-Elmarit 12-60mm f/2.8-4  | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length |
|              |        |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|              |        |                                | Camera, lens and servo motor (for zoom control)  | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|              |        | SUMMILUX 12mm f/1.4            | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length |
|              |        |                                | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |

| Camera Brand           | Model                                    | Lens Model                                       | Mounting Status                                  | Balance Adjustment | Camera Backing Base                               | Servo Zoom/Focus Motor                            | Installation Remark                 |
|------------------------|--|--|--|--------------------|---|---|-------------------------------------|
| BMD                    | BMPPC 4K                                 | 25mm f/1.7                                       | Camera and lens                                  | √                  | -   |   |                                     |
|                        |  |  | Camera, lens and servo motor (for focus control) | √                  | √   | Servo zoom & focus motor installed on either side |                                     |
|                        |  | SUMMILUX 15mm f/1.7                              | Camera and lens                                  | √                  | -   |   |                                     |
|                        |  |  | Camera, lens and servo motor (for focus control) | √                  | √   | Servo zoom & focus motor installed on either side |                                     |
|                        |  | MACRO 30mm f/2.8                                 | Camera and lens                                  | √                  | -   |   |                                     |
|                        |  |  | Camera, lens and servo motor (for focus control) | √                  | √   | Servo zoom & focus motor installed on either side |                                     |
|                        |  | M.ZUIKO DIGITAL ED 12-40mm f/2.8 PRO             | Camera and lens                                  | √                  | -   |   | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for focus control) | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for zoom control)  | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                        |  | M.ZUIKO DIGITAL ED 7-14mm f/2.8 PRO              | Camera and lens                                  | √                  | -   |   | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for focus control) | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for zoom control)  | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                        | M.Zuiko Digital ED 12-100mm f/4.0 IS PRO | Camera and lens                                  | √  | -                  |   | Can be balanced at any focal length               |                                     |
|                        |  | Camera, lens and servo motor (for focus control) | √  | √                  | Servo zoom & focus motor installed on either side | Can be balanced at any focal length               |                                     |
|                        |  | Camera, lens and servo motor (for zoom control)  | √  | √                  | Servo zoom & focus motor installed on either side | Can be balanced at any focal length               |                                     |
|                        | BMPPC 6K                                 | EF 8-15mm f/4L USM                               | Camera and lens                                  | √                  | -   |   | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for focus control) | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for zoom control)  | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                        |  | EF 11-24mm f/4L USM                              | Camera and lens                                  | √                  | -   |   | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for focus control) | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for zoom control)  | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                        |  | EF 16-35mm f/4L IS USM                           | Camera and lens                                  | √                  | -   |   | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for focus control) | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                        |  |  | Camera, lens and servo motor (for zoom control)  | √                  | √   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
| EF 16-35mm f/4L IS USM |  | Camera and lens                                  | √  | -                  |   | Can be balanced at any focal length               |                                     |
|                        |  | Camera, lens and servo motor (for focus control) | √  | √                  | Servo zoom & focus motor installed on either side | Can be balanced at any focal length               |                                     |
|                        |  | Camera, lens and servo motor (for zoom control)  | √  | √                  | Servo zoom & focus motor installed on either side | Can be balanced at any focal length               |                                     |



| Camera Brand      | Model  | Lens Model                   | Mounting Status                                  | Balance Adjustment                                | Camera Backing Base                 | Servo Zoom/Focus Motor                            | Installation Remark                 |
|-------------------|--|------------------------------|--|---|-------------------------------------|---|-------------------------------------|
| BMD               | BMPC6 6K   | EF 16-35mm f/2.8L III USM    | Camera and lens                                  | √   | -                                   |   | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for focus control) | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for zoom control)  | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  | EF 17-40mm f/4L USM          | Camera and lens                                  | √   | -                                   |   | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for focus control) | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for zoom control)  | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  | EF 24-70mm f/2.8L II USM     | Camera and lens                                  | √   | -                                   |   | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for focus control) | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for zoom control)  | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  | EF 24-70mm f/4L IS USM       | Camera and lens                                  | √   | -                                   |   | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for focus control) | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for zoom control)  | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  | EF 24-105mm f/4L IS II USM   | Camera and lens                                  | √   | -                                   |   | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for focus control) | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for zoom control)  | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  | EF 24-105mm f/3.5-5.6 IS STM | Camera and lens                                  | √   | -                                   |   | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for focus control) | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for zoom control)  | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  | EF 24mm f/1.4L II USM        | Camera and lens                                  | √   | -                                   |   | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for focus control) | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  | EF 35mm f/1.4L II USM        | Camera and lens                                  | √   | -                                   |   | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for focus control) | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|                   |  | EF 50mm f/1.2L USM           | Camera and lens                                  | √   | -                                   |   | Can be balanced at any focal length |
|                   |  |                              | Camera, lens and servo motor (for focus control) | √   | √                                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
| EF 50mm f/1.4 USM | Camera and lens                                  | √                            | -  |   | Can be balanced at any focal length |   |                                     |
|                   | Camera, lens and servo motor (for focus control) | √                            | √  | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |   |                                     |
| EF 50mm f/1.8 STM | Camera and lens                                  | √                            | -  |   | Can be balanced at any focal length |   |                                     |
|                   | Camera, lens and servo motor (for focus control) | √                            | √  | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |   |                                     |

| Camera Brand | Model    | Lens Model            | Mounting Status                                  | Balance Adjustment | Camera Backing Base | Servo Zoom/Focus Motor                            | Installation Remark                 |
|--------------|----------|-----------------------|--|--------------------|---------------------|---|-------------------------------------|
| BMD          | BMPCC 6K | EF 85mm f/1.2L II USM | Camera and lens                                  | √                  | √                   |   |                                     |
|              |          |                       | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side |                                     |
|              |          | EF 85mm f/1.4L IS USM | Camera and lens                                  | √                  | -                   |   |                                     |
|              |          |                       | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side |                                     |
|              |          | EF 85mm f/1.8 USM     | Camera and lens                                  | √                  | -                   |   |                                     |
|              |          |                       | Camera, lens and servo motor (for focus control) | √                  | √                   | Servo zoom & focus motor installed on either side |                                     |
|              |          | EF 70-200mm f4 USM    | Camera and lens                                  | √                  | -                   |   | Can be balanced at any focal length |
|              |          |                       | Camera, lens and servo motor (for focus control) | √                  | -                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |
|              |          |                       | Camera, lens and servo motor (for zoom control)  | √                  | -                   | Servo zoom & focus motor installed on either side | Can be balanced at any focal length |

| Camera Brand | Camera Model  | Compatible Lens  | Note   |
|--------------|---------------|--|--|
| RED          | DSMC2 Camera  | The maximum compatible lens is Angenieux 30-90 T2.                     | 1. Cine cameras have multiple modules and different users may have different modules, so the compatible maximum lens may vary from one to another.<br>2. The compatibility list may not include all the compatible cine cameras and lens. Please check with customer service if you have a question. |
| Panasonic    | EVA1          | The maximum compatible lens is Canon EF 70-200mm f4 USM.               |  |
| Sony         | FS5           | The maximum compatible lens is Sony E PZ 18-110mm F4 G OSS.            |  |
|              | FS7           |  |  |
|              | FX9           |  |  |
|              | Z280          | The lens cannot be replaced due to its all-in-one body.                |  |
| Canon        | C200          | The maximum compatible lens is Canon EF 70-200mm f4 USM.               |  |
|              | C300          |  |  |
| ARRI         | Alexa mini    | The compatible lens includes ARRI Ultra Prime series(16mm-100mm lens). |  |
|              | Alexa mini LF |  |  |